

BioPro™ Clamp-On SL

Range of Ultrasound
Flow Sensors



FEATURES & BENEFITS

- ✓ Non-invasive flow measurement of liquids
- ✓ No additional shear stress
- ✓ For use on flexible tubing
- ✓ Fully compatible with the BioPro™ FlowMCP Series and the BioPro™ FlowTrack SL

TECHNICAL SPECIFICATION

	UP TO OD 5/8"	UP TO OD 3/4"	UP TO OD 1-1/8"	UP TO OD 1-5/8"
SIZE (H x W x D)	25 x 33 x 45 mm	28 x 38 x 51 mm	35 x 43 x 69 mm	46 x 56 x 84 mm
WEIGHT TRANSDUCER HEAD	52 g	72 g	140 - 160 g	295 - 315 g
TOTAL WEIGHT (INCL. CABLE AND PLUG)	137 g	153 g	225 - 245 g	380 - 400 g
HOUSING AND LID MATERIAL	Epoxy resin, aluminium, brass		Polymeric compound, aluminum, brass	
CABLE LENGTH	2.9 m ±5 cm Please note: It is possible to adjust the cable length as long as the total cable length does not exceed 4 m (incl. the extension cable).			
IP CODE	Sensor head and cable: IP67 Sensor connector: IP67 in mated condition			
COMPATIBILITY	BioPro™ FlowMCP Series and BioPro™ FlowTrack SL			
CONNECTOR PLUG	16-pin round plug			
EXPECTED PRODUCT LIFE	10 years			
CLEANING AND DISINFECTION	Disinfect easily using alcohol based surface cleaners			

ACCURACY* (IN COMBINATION WITH A BIOPRO™ FLOWMCP AND/OR BIOPRO™ FLOWTRACK SL)

OUTER TUBING DIAMETER (OD)	ACCURACY	RESOLUTION
Up to OD 3/4"	±2 % of reading ±20 ml/min	The resolution depends on the respective measurement system.
Up to OD 7/8"	±2 % of reading ±80 ml/min	
Up to OD 1-1/8"	±2 % of reading ±200 ml/min	
Up to OD 1-5/8"	±2 % of reading ±400 ml/min	

Please note:

The accuracy largely depends on the calibration parameters. The specified accuracies were determined under the following conditions: Medium: Water; Medium Temperature: Calibration Temperature; Straight Inlet Section: 15 x Inner Diameter (ID) of the tube; fully developed flow profile (i.e. system was given time to adjust to atmosphere temperature; tube was fully filled with liquid; steady flow); Tubing: tube the sensor was adjusted and calibrated for.

The installation position of the BioPro™ Clamp-On SL as well as the positioning of pumps and valves within the circuit impact the measurement and must be taken into account when it comes to the accuracy of the BioPro™ Flow Measurement System.

ADJUSTMENT AND CALIBRATION

RECOMMENDED TUBE TYPE	Flexible, non-reinforced tubing, e.g. silicone, PVC
MEDIUM TYPE	Liquids including buffer solutions, cell culture media, fermentation media, hydrocarbons, nutrition media, salines solutions, water, blood, blood substitutes Please note: Due to safety and hygienic reasons, we can only carry out the adjustment using water or, in some cases, glycerol.
MEDIUM OPERATING TEMPERATURE	4 °C to 45 °C (40 °F to 113 °F)
CALIBRATION TABLES	Up to seven calibration tables can be stored to each sensor plug for different applications On-site calibration is possible, as is the use of a customer-specific calibration factor to enhance accuracy

SIZE*	FLOW RANGE 1 [L/MIN]**		FLOW RANGE 2 [L/MIN]**		FLOW RANGE 3 [L/MIN]**		TUBE SIZE***		
	QMIN	QMAX	QMIN	QMAX	QMIN	QMAX	ID [IN]	WT [IN]	OD [IN]
PCT 1/8" x 1/16"	0.017	2.0	–		–		1/8	1/16	1/4
PCT 1/8" x 1/16"	0.017	2.0	0.100	6	–		11/64	3/64	17/64
PCT 3/16" x 1/16"	0.017	2.0	0.100	6	–		3/16	1/16	5/16
PCT 1/4" x 1/16"	0.017	2.0	0.100	8	–		1/4	1/16	3/8
PCT 1/4" x 3/32"	0.017	2.0	0.100	8	–		1/4	1/16	7/16
PCT 3/8" x 1/16"	0.017	2.5	0.100	10	–		3/8	1/8	1/2
PCT 3/8" x 3/32"	0.017	2.5	0.100	10	–		3/8	3/32	9/16
PCT 3/8" x 1/8"	0.017	2.5	0.100	10	–		3/8	1/8	5/8
PCT 1/2" x 3/32"	0.017	2.5	0.100	16.9	2	40	1/2	3/32	11/16
PCT 1/2" x 1/8"	0.017	2.5	0.100	16.9	2	40	1/2	1/8	3/4
PCT 1/2" x 3/16"	0.017	2.5	0.100	16.9	2	40	1/2	3/16	7/8
PCT 3/4" x 1/8"	–		2	75	–		3/4	1/8	1
PCT 3/4" x 3/16"	–		2	75	–		3/4	3/16	1-1/8
PCT 1" x 1/8"	–		2	100	–		1	1/8	1-1/4
PCT 1" x 3/16"	–		2	100	–		1	3/16	1-3/8
PCT 1-1/4" x 3/16"	–		2	100	–		1-1/4	3/16	1-5/8

* Custom sizes are available upon request.

*** ID = Inner Diameter; WT = Wall Thickness; OD = Outer Diameter

**Please note:

Customized flow ranges must be requested and checked regarding their feasibility.

While a measurement is possible outside the given flow measurement range, the accuracy indicated above is only valid within that range. The possible low rate also depends on the tubing.

AMBIENT CONDITIONS DURING TRANSPORT, STORAGE, AND OPERATION

TRANSPORT AND STORAGE

ATMOSPHERIC PRESSURE	70 kPa to 106 kPa
TEMPERATURE RANGE TRANSPORT AND STORAGE	-20 °C to 55 °C (-4 °F to 131 °F)
TEMPERATURE RANGE OPERATION	10 °C to 40 °C (50 °F to 104 °F)
RELATIVE HUMIDITY	10 % to 96 % (non-condensing)

DESIGN FOR LIFE



WARNING: The customer is solely responsible for determining the necessary or most suitable product or service for any particular use case or application. All such risks are assumed by the customer. Specifications subject to change without notice.
WARRANTY: For product warranty information, please contact: info@cpc-bio.com or +1 800-519-7633.
 For trademark information, please visit: www.cpc-bio.com/trademarks-and-patents
 © 2026 CPC BIOTECH. ALL RIGHTS RESERVED.
 FMS-BPCO-SS-26001

CPC BIOTECH | EM-TEC GMBH
 Lerchenberg 20
 86923 Finning, Germany
 Phone: +49 8806 9236 0
 Email: info@cpc-bio.com

cpc-bio.com